



18375 Bandilier Circle, Fountain Valley, CA, 92708 Tel: 714 965-7828 Fax: 714 965-7829

Installation Instructions

Part No. 5CF 001 00, 6CF 001 00, 6CF 002 0R, 6CF 002 1R

2.0" & 2.5" Front Coil-Over Kit

2004+ Ford F150 2WD & 4WD

Enclosed Parts List:

(2) Coil Over Shock Assemblies

(6) 3/8" Washers

(6) 3/8"- 16 Lock Nuts

(4) Bearing Spacers (Attached to lower rod-end)

Radflo Suspension Technology recommends that all products are installed by trained professionals.

*****Please read instructions thoroughly before proceeding with installation*****

Radflo shocks come pre-charged with the correct amount of nitrogen. Please do not release pressure.

INSTALLATION INSTRUCTIONS:

1. Please ensure that the vehicle is turned off and in park and the wheels are chocked.
2. Measure from the center of the hub to the bottom of the fender opening and record this for future reference.
3. Jack up the vehicle and place on jack stands. Remove front wheels.
4. Loosen the nut on the outer tie rod. With a large hammer strike the end to dislodge the taper. Remove the nut and move tie rod out of the way.
5. Remove the 3 nuts on the stock upper coil-over mount. **Do not loosen the center nut as this secures the coil spring to the shock.**
6. Remove the bar pin from the lower control arm.
7. Remove the stock coil-over. You may have to use a pry bar to pry the control arms apart in order to remove the shock.
8. Install new coil-over upper mount utilizing supplied hardware.
9. Install the lower shock mount to the lower control arm utilizing the stock bolt.
10. Re-install the outer tie rod. Torque nut to 55 foot pounds and re-install cotter pin.
11. Install the wheels and lower the vehicle to the ground. Drive the vehicle backward and forward to settle the suspension. The install is now complete.
12. Measure from the center of the hub to the bottom of the fender opening. Compare measurements to step #2.
13. To adjust the coil-overs both front wheels need to be drooped completely. There is no need to remove the wheels. Use a C-Spanner wrench (not supplied) to loosen the top lock collar of the adjustment ring. Using the wrench rotate the adjustment collar down for additional lift or up for less lift. The lift will be approximately double the distance the



18375 Bandilier Circle, Fountain Valley, CA, 92708 Tel: 714 965-7828 Fax: 714 965-7829

collar is moved. Once the desired lift is reached tighten the lock collar on the adjustment collar again. Tip:- Using some lubrication on the thread and collar will make it easier to adjust.

For technical support please contact Radflo Suspension Technology directly at (714) 965-7828 Monday - Friday 8:00 am - 5:00 pm Pacific time. Thank you for your purchase of Radflo Suspension Technology products.

Please retain all stock components if you ever have the need to remove your Radflo suspension products.